



Husqvarna TS 112

Intuitive operation and exceptional cutting results for large open lawns. The compact design enables effortless navigation in narrow passages and compact storage while not in use. A convenient and hassle-free mowing experience thanks to easy access levers and side-by-side pedal placement that enables mowing in reverse. Enjoy signature Husqvarna quality and durability for a garden tractor you can rely on.



Adjustable driver seat

Tool-less adjustment of seat position.



Dual headlights

Dual headlights at the front.

Hour meter

Helps you having control over service and maintenance intervals.



Ergonomic driving position

Easy-access controls and plenty of leg room thanks to the adjustable seat. The spring assisted height adjustment cutting deck makes it easy to operate.



FEATURES

- Helps you having control over service and maintenance intervals.
- Dual headlights at the front.
- Tool-less adjustment of seat position.
- Easy-access controls and plenty of leg room thanks to the adjustable seat.The spring assisted height adjustment cutting deck makes it easy to operate.
- Equipped with a 95cm side discharge cutting deck.
- The cutting deck is equipped with anti-scalp wheels, which reduce the risk of scalping when cutting uneven lawns.
- Compact design for effortless navigation in narrow passages and easy storage while not in use.
- Safe and convenient access to the mow in reverse functionality.
- Fuel level window makes it easy to check the fuel level.
- Lever to engage the cutting deck.
- Dual pedal drive for better drive control and easy, intuitive operation.
- Controls levers on one side make it easier to get in and out of the seat.
- Towing hook Included for multiple rear attachments.
- Easy speed and direction control with pedal-operated hydrostatic transmission. Separate pedals for forward and reverse.
- Turn key start
- Easy accessible cutting height adjustment for improved ergonomics. The spring-assisted cutting deck makes adjustment easier.

Technical Specifications	
ACCU	
Accu capaciteit	20 Ah
Accuspanning	12 V
CAPACITEIT	
Netto vermogen bij afgesteld toerental, kW	Revolutions per minute
Uitgangsvermogen	2800 t/pm
AFMETINGEN	
Maaihogte-instelling	Gemonteerde bumper
Maaihogten instelling	Lever, while seated
Maaihogten	6
Maaibreedte	95 cm
Rugleuning hoogte	Medium
Bandenmaat, voor	15x6-6
Bandenmaat, achter	18x8.5-8
MOTOR	
Cilinders	1
Cilinder inhoud	413 cm³
Motor merk	Husqvarna
Koeling motor	Lucht
Type motor	HS 413AE
Generator	12 A
Motor	Husqvarna
Motor/engine model(nieuw)	HS 413AE
Transmissie fabrikant	Hydro-Gear
Transmissie model	T2
Versnelling, type	Hydrostatische
Benzinetank inhoud	6 l
Volume brandstoftank	1.59 gal (VS)
UITRUSTING	
Type luchtfilter	Cartridge met een voorfilter
Anti-scalp wielen	2
BioClip® kit	Verkrijgbaar als accessoire
Mesinschakeling	Manueel
Messen type	Discharge
Messen	2 stuks
Opvangbak	Verkrijgbaar als accessoire
Bekerhouder	Ja
Maaidek type	Stamped
Maaimethodes	Verzamelen/BioClip®/zijkant uitwerpen
Waspoort maaidek	Ja
Deflector	No
Rijmethode	Dual pedal-operation
Voorzijde bescherming	Available as accessory
Generator	12 A
Koplampen	Ja
Urenteller	Digitaal
Mulch inzetstuk	Verkrijgbaar als accessoire
Poedergecoat maaidek	Nee
Zitting type	Standaard
SMEERMIDDEL	
Motorolie type	Druk
Positie brandstoftank	Voorzijde
Oliefilter	Nee
Type brandstof	Petrol
MATERIALEN	
Materiaal maaidek	Staal

Technical Specifications	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
Materiaal steel	PU
VERPAKKING	
Verpakkingshoogte	850 mm
Verpakkingslengte	1700 mm
Verpakkingsbreedte	1135 mm
Hoeveelheid in omverpakking	1

ACCESSORIES



AFDEKZEIL VOOR TRACTOR
505 63 08-80



MULCH COVER
538 89 88-01



ACCULADER BC 0.8
579 45 01-01



TRAILER
967 02 71-01



STROOIER 30
589 40 93-01



BELUCHTER
586 63 67-02



VERTICUTEERHARK
586 63 66-01



TRACTOR BUMPER
538 89 94-01



TRAILER 275
501 00 82-01



GRINDEG
953 51 24-01



OPRIJPLATEN
505 69 90-41



OPRIJPLATEN
505 69 90-43



OPRIJPLATEN
505 69 90-40